



* The information, descriptions, designs and suggestions provided by LXBD, verbally or written, are exclusively given for your guidance only, owing to many factors out of LXBD control, which are susceptible to affect the process, applications or product uses; it must be necessary executing by the user the necessary tests to establish the suitability of the products for particular purpose prior to be used. LXBD suggestions don't exclude the user obligation to check the technical data sheets and safety data sheets, just as our informative brochures. No warranties of any kind, either implied or explicit, including the implied warranties of marketability, capacity for a particular purpose may be considered like a license concession to infringing rights derived of current patents. In any case the descriptions, data and designs shown here, should not be understood as elements of our terms and sale conditions. The user agrees and expresses to know that neither of the descriptions and data given by LXBD can be considered as assumption of obligation and/or responsibility of this society, with regard the results obtaining as particular uses of product; results that are accepted by the user under his own responsibility.

Nov 24



HUMAN TEAM



SUSTAINABLE
DEVELOPMENT



COMPANY VALUE



ENVIRONMENTAL
RESPONSIBILITY



INNOVATIVE



LXBD

CONSTRUCTION

EMULSIONS GUIDELINE | PRODUCT RANGE



PROPERTIES

NATURE
(Type)

PARAMETERS

PROTECTOR COLLOID

TOTAL SOLID CONTENT (%)

VISCOSITY
BROOKFIELD RVT
(50 rpm, 23°C) (mPa·s)

pH

Tg (°C)

ADHESIVES

FAMACRIL C-13 ★	Bonding primer for mortars and gypsum with permanent tack.	V / A
FAMACRIL C-135 ★	Bonding primer for substrates with low or no porosity.	S / A

CEMENTITIOUS APPLICATIONS

FAMACRIL C-24 ★	2C Elastic mortars, good adhesión and excellent elasticity.	S / A
FAMACRIL C-47 ★	Mortar modifier. It provides hardness, durability, resistance and adhesion. Especially recommended for the bonding of new to old concrete.	A

BINDERS-VARNISHES

FAMACRIL C-620 ★	Stamp pavement varnish. Early water resistance and good abrasion resistance.	A
------------------	--	---

THICKENER

FAMACRIL TH-22 ★	Acrylic thickener (ASE).	A
------------------	--------------------------	---

An	53 ± 1	< 600	3,0-5,0	- 50
An	50 ± 1	1.000-3.500 *	7,5-9,0	- 5

An	58 ± 1	500 - 1.200 *	7,5-9,5	- 15
An	64 ± 1	500 - 1.500*	6,5-8,0	- 35

An	40 ± 1	< 100	7,0-8,0	39
----	--------	-------	---------	----

An	25 ± 1	< 100	2,0-3,0	-
----	--------	-------	---------	---



★ Alkylphenol ethoxylates free

ASE : Alkali swellable emulsion (alkali soluble)

V/ V = Vinyl-Versatate

S/A = Styrene-Acrylic

A = Acrylic

An: Anionic

(*) Viscosity Brookfield RVT 50 rpm, 23°C

LXBD

Construction